

BEST AVAILABLE COPY


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F15C 1/04, F17D 1/16, G05D 7/06		A1	(11) International Publication Number: WO 99/57444
			(43) International Publication Date: 11 November 1999 (11.11.99)
(21) International Application Number: PCT/NO99/00142		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 30 April 1999 (30.04.99)		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. In English translation (filed in Norwegian).	
(30) Priority Data: 19981986 30 April 1998 (30.04.98) NO			
(71) Applicant (for all designated States except US): APPLIED PLASMA PHYSICS AS [NO/NO]; Postboks 584, N-4305 Sandnes (NO).			
(72) Inventors; and (75) Inventors/Applicants (for US only): JOHNSEN, Torfinn [NO/NO]; Hordaveien 4, N-4307 Sandnes (NO). NÆSJE, Kjetil [NO/NO]; Askeveien 8, N-4314 Sandnes (NO).			
(74) Agent: ONSAGERS PATENTKONTOR - DEFENSOR AS; P.O. Box 265, Sentrum, N-0103 Oslo (NO).			

(54) Title: METHOD FOR REDUCING PRESSURE LOSS IN CONNECTION WITH TRANSPORT OF FLUID IN PIPES/DUCTS



(57) Abstract

A method is described for controlling pressure loss in connection with transportation of fluid in a pipeline (1) by controlling electrical charge concentration in fluid and/or pipeline. According to the invention the fluid is supplied with an electrical charge from at least one electrode (2, 3) arranged in the pipeline (1), at least the pipeline's (1) inner wall being made of a material which is capable of absorbing a charge from the fluid and retaining this charge, with the result that the amount of similar charges in the pipeline's (1) wall and the fluid is increased, thereby creating electrical repulsive forces between fluid and pipe wall. By this means the friction between pipe wall and fluid is reduced.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WO 99/57444

PCT/NO99/00142

1

method for reducing pressure loss in connection with transport of fluid in pipes/ducts

The present invention relates to a method for reducing pressure loss in a cost-effective, safe and energy-effective manner and thereby investment and operating costs in connection with transport of fluids in pipes/ducts.

A familiar and serious problem for all those who are involved in transporting fluids in pipes/ducts is that in many cases this transport is expensive and energy-demanding on account of pressure loss due to friction between the fluids and the pipe/duct. A method for cost-effectively reducing pressure loss in connection with pipe flows will therefore be of great value.

From US 4,254,800 it is known that it is possible to supply an electrical charge to a fluid which is transported in a pipe and subsequently expose the fluid to electrostatic or magnetic forces in order to regulate the through-flow of the fluid. In this publication, however, it is only described how this can be used to reduce the through-flow by the described apparatus acting as a valve at a given location in the pipe.

The task of the present invention is to provide a method for reducing the pressure drop in a pipeline where a fluid is transported over substantial distances and where the result of the pressure drop is that it is energy-demanding to pump the fluid through the pipeline. Thus a reduction in the pressure drop will lead to a corresponding reduction in the energy consumption during the fluid transport.

These objectives are achieved by employing the methods according to claim 1. The remaining claims describe advantageous embodiments of the method.

It is a well-known fact in physics that an important factor for determining which pressure level is necessary for maintaining fluid flow in pipes is the friction between fluid and pipe. It is further known from classic electrostatics that similar charges repel each other and dissimilar charges attract each other. According to classic fluid mechanics and electrostatics, therefore, the friction between fluid and pipe/duct and thereby the pressure which is required to maintain the flow will be dependent on net electrical charge in fluid and pipe/duct. Increased similar net charges in fluid and pipe/duct will reduce pressure loss since electrical repulsive forces near the pipe wall will

WO 99/57444

PCT/NO99/00142

2

reduce the contact surface and thereby the friction between fluid and pipe/duct while increased dissimilar net charges will increase the pressure loss.

5 It has been found that the above-mentioned physical laws can be applied and that pressure loss in connection with pipe flow can be controlled by controlling the net charge in pipe/duct and fluid. According to the invention, therefore, the pressure loss can be reduced by increasing the amount of similar charges in pipe/duct and fluid, and the pressure loss increased by
10 reducing the amount of similar charges in pipe/duct and fluid or increasing the amount of dissimilar charges. This requires the pipe wall to be made of an insulating material or at least one which is a poor conductor of electricity, such as teflon or another "flow coating" which is used for oil transport. The fluid moreover must be insulating or at least dielectric. In other words, the method can be used for hydrocarbons and gases, but not for water.

15 In a preferred embodiment of the invention the pipe/duct is formed from a material with adapted electrical conductivity properties, thus enabling the pipe/duct to retain a supplied net charge. The pipe/duct and/or fluid is then supplied with a net charge with the desired polarity by connecting it or them to a suitable power and/or voltage generator.

20 In a further preferred embodiment optimal pressure drop is achieved by controlling the space charge distribution in the fluid by extending a thin electrode (small contact surface) in the fluid flow's longitudinal direction, which electrode is coupled to the power and/or voltage generator.

25 The invention will now be described in further detail with reference to the attached drawings, in which

Fig. 1 is a schematic representation of the principle design of the invention,

Fig. 2 is an alternative design of an electrode for use in implementation of the method.

30 Figure 1 illustrates the principle construction of an embodiment of the method according to the invention. In a pipeline 1 in which fluid is transported the pipe wall, or at least the pipe wall's internal surface, is made of a material which is capable of absorbing and retaining electrical charges, but which is a poor conductor of electricity. Examples of such materials are

WO 99/57444

PCT/NO99/00142

3

teflon and other "flow coating" which are employed in oil transportation. In order to supply the fluid with an electrical charge, an electrode grid 2 can be arranged across the direction of flow and/or a longitudinal electrode 3 can be provided which in this example is provided as a centre electrode in the pipeline. By means of these electrodes 2, 3 the fluid will absorb an electrical charge. For its part the fluid will emit a charge to the pipeline's 1 inner wall. On account of its poor electrical conductivity, and possibly also due to the fact that the pipeline is insulated from earth, the pipeline's inner wall will not emit a charge as quickly as it absorbs a charge before both fluid and pipeline are charged with charges with the same sign. In other words, electrical repulsive forces will be created between pipe wall and fluid, thus reducing the friction between fluid and the pipeline's inner wall.

The electrode grid 2 and the centre electrode 3 will preferably be made of a conducting or semi-conducting material of great durability. A suitable material for this purpose is stainless steel. It is necessary for the centre electrode 3 to be attached in such a manner that it remains substantially centred in the pipeline. This can be implemented by means of a stay 4 which preferably is electrically insulated from the centre electrode, and which in other respects is designed so as to offer the least possible flow resistance to the fluid. If there is an electrode grid 2 it should also be designed so that it does not offer any marked flow resistance to the fluid which is transported in the pipeline 1.

For supplying a charge to the fluid the electrodes 2, 3 are connected to one pole of a power or voltage source 5 whose other pole is connected to earth. In order to supply an adequate charge the voltage source should preferably have a voltage level of between 1kV and 150kV. In some cases it may also be appropriate to have even higher voltage levels. This will vary according to what kind of fluid is being transported in the pipeline 1, the diameter of the pipeline 1, the fluid's flow rate, the pipe wall's ability to absorb and retain a charge, etc., and must be adapted in each individual case. The voltage which is supplied to the electrodes will preferably be direct voltage, but it may also be appropriate to use voltage pulses. Any overlaying of a direct voltage with voltage pulses (ripples) will be able to influence the fluid's ionic properties, thus giving the system improved efficiency with lower voltages. Again the choice of voltage levels as well as pulse duration and frequency will depend on the characteristics of the different remaining parts of the system, such as

WO 99/57444

PCT/NO99/00142

4

for example fluid and pipeline, and a person skilled in the art must select those values which are most effective in each individual case.

Figure 2 illustrates a detail of a system corresponding to that in figure 1, but where the longitudinal electrode 3 is in the form of a spiral which is arranged at a relatively short distance from the pipeline's 1 inner wall. In this embodiment a charge will be emitted to the fluid at a short distance from the pipe wall, and the transport of the charge from the fluid to the pipe wall will be more effective. Furthermore, the ion flow will generate some heat, leading to a certain increase in temperature in the fluid, which will have a positive effect on the fluid's viscosity. In a possible embodiment of the method according to the invention the electrode's electrical resistance and/or the power/voltage level from the power supply 5 will be chosen so as to create further heating. Again it will be dependent on external circumstances, such as for example the fluid's characteristics, whether consumption of energy for such heating provides a net energy gain when transporting fluid through the pipeline. This in turn will be a question of technical adaptations of the method in order to obtain the most efficient system possible.

WO 99/57444

PCT/NO99/00142

5

PATENT CLAIMS

1. A method for controlling pressure loss in connection with fluid flow in pipelines,
characterized in that the charge concentration in the pipeline (1) and the fluid
5 is controlled by providing at least one electrode (2, 3) in the pipeline (1) and
that a voltage is applied to this at least one electrode (2, 3) with the result
that when the fluid passes this at least one electrode (2, 3) the electrical
charge is emitted to the fluid, the fluid further emitting the charge to the pipe
wall, thus increasing the amount of similar charges in the pipeline's (1) wall
10 and the fluid.
2. A method according to claim 1,
characterized in that at least the pipeline's (1) inner wall is made of a
material with adapted electrical conductivity characteristics, thus enabling it
to absorb and retain the supplied net charge.
- 15 3. A method according to claim 2,
characterized in that the said material is teflon.
4. A method according to one of the preceding claims,
characterized in that the voltage which is applied to the at least one electrode
is at least 1kV.
- 20 5. A method according to one of the preceding claims,
characterized in that the voltage which is applied to the at least one electrode
is in the range 1kV to 150kV.
6. A method according to one of the preceding claims,
characterized in that as the at least one electrode (2, 3) an electrode grid (2)
25 is employed which is arranged across the fluid's direction of flow.
7. A method according to one of the preceding claims,
characterized in that as the at least one electrode (2, 3) an electrode (3) is
employed which is arranged in the pipeline's (1) longitudinal direction.
8. A method according to claim 7,
30 characterized in that the electrode (3) arranged in the pipeline's (1)

WO 99/57444

PCT/NO99/00142

6



longitudinal direction is a centre electrode with a small diameter and arranged along the pipeline's (1) centre axis (figure 1).

9. A method according to claim 7, characterized in that the electrode (3) arranged in the pipeline's (1) longitudinal direction is in the form of a spiral which is disposed at a short distance from the pipeline's (1) inner wall.

10. A method according to one of the preceding claims, characterized in that the at least one electrode's (2, 3) electrical characteristics and power/voltage level which are applied thereto are so selected that sufficient heat is emitted from the at least one electrode (2, 3) to increase the temperature of the fluid, thereby changing its viscosity.

WO 99/57444

PCT/NO99/00142



1

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 99/00142

A. CLASSIFICATION OF SUBJECT MATTER		
IPC6: F15C 1/04, F17D 1/16, G05D 7/06 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC6: F15C, G05D, F17D		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
SE,DK,FI,NO classes as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4254800 A (KENJI MASAKI), 10 March 1981 (10.03.81), column 3, line 12 - line 35	1-7
X	GB 1385551 A (LENINGRADSKY ORDENA LENINA POLITEKHNICHESKY INSTITUT IMENI M.I. KALININA), 26 February 1975 (26.02.75), claims 1-4	1,7
X	US 4203398 A (HIROYUKI MARUOKA), 20 May 1980 (20.05.80), column 2, line 24 - line 55	1,4-6
A	DE 3233838 A1 (WSW PLANUNGSGESELLSCHAFT MBH), 15 March 1984 (15.03.84), abstract	1,3
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
28 Sept. 1999		07-10-1999
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86		Authorized officer Lars Jakobsson/AE Telephone No. +46 8 782 25 00

Form PCT/ISA/210 (second sheet) (July 1992)

2

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 99/00142

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P	WO 9919260 A1 (WASKAAS, MAGNE), 22 April 1999 (22.04.99), abstract -----	1

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT
 Information on patent family members

30/08/99

International application No.

PCT/NO 99/00142

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4254800 A	10/03/81	NONE	
GB 1385551 A	26/02/75	NONE	
US 4203398 A	20/05/80	CA 1109545 A DE 2720523 A,C GB 1571201 A JP 52135988 A JP 53000390 A JP 53001324 A	22/09/81 24/11/77 09/07/80 14/11/77 05/01/78 09/01/78
DE 3233838 A1	15/03/84	NONE	
WO 9919260 A1	22/04/99	AU 9561898 A NO 974715 A	03/05/99 12/04/99

Form PCT/ISA/210 (patent family annex) (July 1992)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☒ FADED TEXT OR DRAWING

☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☒ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.